

The Belcom logo features the word "Belcom" in a bold, black, sans-serif font. To the right of the text is a stylized red swoosh that curves upwards and then downwards, resembling a signal or a cable. The background of the entire page is a light blue gradient with abstract white and red circular patterns.

PR14316-1

Low Loss Flexible Communication Coax 75Ω

High performance Low Loss range suitable for satellite , video applications – CCTV , CATV , baseband or broadband . Far more flexible than any corrugated solution

This versatile range is available in a number of sizes with FireFighter® Low Smoke Zero Halogen sheath according to IEC60332-3-24 as standard. PE sheathed and steel wire armoured versions are available on request.



 01279 871129

 01279 871150

 sales@belcom.co.uk

 www.belcom.co.uk

Low Loss Flexible Communication Coax 75 Ω

Cable Guide



Coax Type		200	240	300	400	600
Physical Characteristics						
Inner Conductor		Solid plain copper	Solid plain copper	Solid plain copper	Solid plain copper	Solid CCA
Diameter	mm	0,60	0,80	1,15	1,65	2,74
Dielectric		Foam PE	Foam PE	Foam PE	Foam PE	Foam PE
Diameter	mm	2,80	3,65	5,10	7,20	11,56
Shield		Aluminium tape	Aluminium tape	Aluminium tape	Aluminium tape	Aluminium tape
Diameter	mm	2,90	3,75	5,20	7,30	11,71
Braid		TCWB	TCWB	TCWB	TCWB	TCWB
Diameter	mm	3,30	4,35	5,60	7,90	12,45
Outer Jacket		LSZH	LSZH	LSZH	LSZH	LSZH
Diameter	mm	4,50	6,00	6,80	10,10	14,99
Part Number						
LSZH FireFighter®		200754	240754	300754	400754	600754

PE : Polyethylene

LSZH : Low Smoke Zero Halogen FireFighter®

TCWB : Tinned Copper Wire Braid

CCA: Copper Clad Aluminium